

KNOWLEDGE BASE · PUBLIC DOCUMENT

n8n workflow failed: reading the error, retrying and getting an alert

Automation & n8n

CODE

RLX-INT-KB-3288

VERSION

v2026.10.10

COUNTRY · LANGUAGE

International · English

MozOut International

RLX Holdings (Pty) Ltd. · Group RLX Holdings

Tax no. (SARS) 943 907 6234 · Registration no. (CIPC) 2025/667953/07

<https://www.my.mozout.com/knowledgebase/3288>



When an n8n workflow fails, the **executions** list shows which one and at what node. From there you have three tools to make it robust: **retrying** on the node, deciding **what to do on error**, and an **error workflow** that sends you a notice. n8n is third-party software running on your VPS; the exact screen names depend on the version, so confirm in the project's documentation.

First, read the error

1

Open the executions list and find the one marked as failed. Open it.

2

Find the red node. It is the one that failed. The nodes before it ran fine.

3

Read the message and the data that went into that node. It nearly always explains: an empty field, a refused credential, a request that took too long.

4

Reproduce it with the same data. You can run just that node, to test the fix without repeating the whole workflow.

The three defences

Defence	What it is for	When to use it
Retry on fail (in the node's settings)	Tries the same node again a few times, with a pause between tries.	Passing failures: a slow network, a busy API, a request limit.
What to do on error (in the node's settings)	Stop the workflow, or carry on with the rest of the data and handle the error separately.	When an error on one row should not stop the others.
Error workflow	A separate workflow, with the error trigger, that runs when another one fails.	To get the notice: e-mail, message, a row in a sheet.

Building the alert

1

Create a new workflow that starts with the error trigger. Then add a node that sends you a message (e-mail or Telegram). See **alerts to Telegram**.

2

Put in the notice the name of the workflow that failed, the node, the error message and the time.

3

In the settings of each important workflow, choose that workflow as the error workflow. Link it to all of them, or the ones you miss fail silently.

4

Cause a failure on purpose in a test workflow and see whether the notice arrives.

Retrying is not for everything. If the node sends a message or creates an order, retrying can duplicate the effect: the customer gets it twice. On those nodes, retry only if the service accepts an identifier that prevents duplicates, or handle the error by hand.

If n8n stops answering or restarts by itself, the problem may not be the workflow: see **n8n running out of memory: the causes**. If the trigger never fires, see **n8n webhooks: test URL, production URL, and why they do not fire**.

Clear old executions. They keep the data that passed through, and that fills the disk and holds customer data longer than you need. Set how long you keep them.

Need a server for your workflows? See the VPS plans.

[See the VPS servers](#)

SEE ALSO

[n8n running out of memory: the causes](#)

[n8n webhooks: test URL, production URL, and why they do not fire](#)

[Securing n8n: access, credentials and exposed webhooks](#)



Online version of this document

MozOut is a leading internet services company, with a mission to help businesses to be born and prosper through technology.

2020

FOUNDED

37,000+

CLIENTS

130+

SIGN-UPS A DAY

MozOut International

RLX Holdings (Pty) Ltd. • Group RLX Holdings

TAX NO. (SARS)

943 907 6234

REGISTRATION NO.
(CIPC)

2025/667953/07

REGISTERED OFFICE

1111 Olive Street
Saint Louis 63101, Missouri, United States

CONTACT

info@mozout.com • +27 78 823 3325 • www.mozout.com

OPENING HOURS

Monday to Friday - 08 AM to 04 PM
Saturday & Sunday - Closed