Mozout

Generated on 28/11/2026 21:11

KNOWLEDGE BASE · PUBLIC DOCUMENT

Listing your agents through the API: type=agent, base_model and status

Agents Through the API

CODE	VERSION	COUNTRY · LANGUAGE
RLX-INT-KB-9240	v2026.11.28	International · English

MozOut International
RLX Holdings (Pty) Ltd. · Group RLX Holdings
Tax no. (SARS) 943 907 6234 · Registration no. (CIPC) 2025/667953/07

https://www.my.mozout.com/knowledgebase/9240

Listing your agents through the API: type=agent, base_model and status

Agents Through the API Created on **November 28, 2026** 2 min read



The API model list, `GET /v1/models`, also includes your agents, before the models. With `type=agent`, it returns only the agents. You need a key with `ai:read`, and listing spends no credits.

The request

On Linux and macOS:

```
curl "https://api.mozout.com/v1/models?type=agent" -H "Authorization: Bearer $MOZOUT_API_KEY"
```

In Windows PowerShell:

```
curl.exe "https://api.mozout.com/v1/models?type=agent" -H "Authorization: Bearer $env:MOZOUT_API_KEY"
```

The list follows the OpenAI format, so the SDK's `client.models.list()` works too. In Python, with the filter:

```
import os
from openai import OpenAI

client = OpenAI(base_url="https://api.mozout.com/v1", api_key=os.environ["MOZOUT_API_KEY"])

for m in client.models.list(extra_query={"type": "agent"}):
    print(m.id, getattr(m, "status", None), getattr(m, "base_model", None))
```

What comes with each agent

```
{
  "id": "agent/7c1e9a42-b35d8f06-a2c4e719-5d0b3f8e",
  "object": "model",
```

```
  "owned_by": "user",
  "type": "agent",
  "category": "agent",
  "name": "Support assistant",
  "description": "Answers customer questions about our plans.",
  "base_model": "deepseek-ai/deepseek-v4-flash",
  "status": "active",
  "tools": ["web_fetch", "current_datetime"],
   "pricing": { "unit": "1M tokens", "input": 56.0, "output": 112.0, "cached_input": 11.2 }
}
```


Field	What it says
`id`	The value to put in `model` in chat requests: `agent/` and the agent id.
`type`	Always `agent`.
`name` and `description`	The name and description you gave the agent in All in One AI.
`base_model`	The text model the agent uses.
`pricing`	That model's price, in credits per 1 million tokens. The agent has no price of its own.
`tools`	The tools turned on: `web_fetch`, `web_search` and `current_datetime`.
`status`	`active` or `paused`.

Each account only sees its own agents. The list is the same with a `sandbox_` key and with a `prod_` key.

What it is for

1. Checking the right id before you put it in a program.
2. Seeing whether an agent is paused before you open the website chat.
3. Showing your agents in an app of your own, so someone can pick one.
4. Knowing the price per token, from the `pricing` of the agent's model.

On the MCP server, the `list_models` tool also accepts the `agent` type. See **talking to your agent through MCP**.

RECOMMENDED

Want to use your agents in your own programs? See All in One AI.

See All in One AI →

SEE ALSO

- **Using your AI agent through the API: agent/ in the model field**
- **Pausing, turning back on or deleting an agent, and the agent_paused error**
- **Agent errors through the API: agent_paused and model_not_found**
- **Choosing a text model: price, context window and what each one is for**
- **All in One AI**

Mozout

MozOut International

RLX Holdings (Pty) Ltd. · Group RLX Holdings

TAX NO. (SARS)	943 907 6234
REGISTRATION NO. (CIPC)	2025/667953/07
REGISTERED OFFICE	1111 Olive Street Saint Louis 63101, Missouri, United States
CONTACT	info@mozout.com · +27 78 823 3325 · www.mozout.com
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-INT-KB-9240 · v2026.11.28 · Generated on 28/11/2026 21:11