Mozout

Generated on 28/11/2026 21:33

KNOWLEDGE BASE · PUBLIC DOCUMENT

Codex in a project: why .codex/config.toml cannot change the provider

Codex CLI


CODE	VERSION	COUNTRY · LANGUAGE
RLX-INT-KB-9474	v2026.11.28	International · English

MozOut International
RLX Holdings (Pty) Ltd. · Group RLX Holdings
Tax no. (SARS) 943 907 6234 · Registration no. (CIPC) 2025/667953/07

https://www.my.mozout.com/knowledgebase/9474

Codex in a project: why .codex/config.toml cannot change the provider

Codex CLI Created on **November 28, 2026** 2 min read



Besides your user file, Codex reads `.codex/config.toml` files inside projects. They hold the team settings. But there are keys Codex does not accept there, and the provider is one of them.

What Codex ignores in a project

According to the official documentation, a project `.codex/config.toml` cannot change `model_provider` or `model_providers`. Codex ignores them and shows a warning at start. The same goes for `openai_base_url`, `profile`, `profiles`, `notify` and `otel`, among others.

The provider and the authentication are settings of each computer. That way, a repository you cloned cannot send your requests, or your key, to another address.

Where each thing goes

File	What it can hold
`~/.codex/config.toml` **(on Windows,** `%USERPROFILE%\.codex\config.toml` **)**	The MozOut provider, with `base_url`, `env_key` and `wire_api`, and the starting model.
`.codex/config.toml`**, in the project**	The model and other project settings. No provider and no key.

Choosing the model for a project

The project can choose the model, and Codex uses it with the provider from your user file. At the project root, create `.codex/config.toml` with just this line:

```
model = "zai-org/glm-5.2"
```

Codex looks for `.codex/config.toml` from the project root down to the folder you are in. If there is more than one, the closest wins. And it only reads these files in a project marked as trusted.

The Codex order

When the same key is in several places, Codex follows this order, from the one that counts most to the one that counts least:

1. Command-line options, such as `-m` and `-c`.
2. The project `.codex/config.toml` files, the closest first.
3. The profile chosen with `--profile`.
4. Your `~/.codex/config.toml`.

! Did you see the warning that Codex ignored `model_provider`? The provider is in the wrong file. Move the `[model_providers.api]` block and the `model_provider` line to `~/.codex/config.toml` and leave only `model` in the project.

RECOMMENDED

Want to code with AI in Codex? Visit the Coding with AI page.

See Coding with AI →

SEE ALSO

- Codex CLI with All in One AI: creating config.toml, the key and the model →
- Naming the provider in Codex: the reserved names openai, ollama and lmstudio →
- Using another model for one Codex session: codex -m →
- env_key in Codex: how it reads your key from an environment variable →
- Coding with AI in All in One AI →

Mozout

MozOut International

RLX Holdings (Pty) Ltd. · Group RLX Holdings

TAX NO. (SARS)	943 907 6234
REGISTRATION NO. (CIPC)	2025/667953/07
REGISTERED OFFICE	1111 Olive Street Saint Louis 63101, Missouri, United States
CONTACT	info@mozout.com · +27 78 823 3325 · www.mozout.com
OPENING HOURS	Monday to Friday - 08 AM to 04 PM Saturday & Sunday - Closed

Online version of this document

RLX-INT-KB-9474 · v2026.11.28 · Generated on 28/11/2026 21:33